

DHO 40-275(1+0)-FM

Grade II, Type 2
Location of use: Distribution box
Power supply system: TN-S,TT,IT
Nominal Discharge Current (In): 20 kA(8/20μs) T2
Max. Discharge Current (Imax): 40 kA(8/20μs) T2
Protective Element: High Energy MOV
Housing Design: Plug-in module and separate base design
Housing Material: PA 66 UL 94 V-0
Certification Marks:



Rated voltage Un	230 V AC
Max. continues operating voltage Uc	275 VAC (L-PE)
Rated operational voltage Uo	220 V AC
Rated operational voltage Ue	230 V AC
Rated frequency f	50/60 Hz
Residual current(PE) IPE	≤ 5 μA
Short-circuit current tolerance	300 A
Current type	AC
Nominal discharge current In (8/20μs)	20 kA T2
Max. discharge current Imax (8/20μs)	40 kA T2
Protection level Up	
L-PE At In impuls current	≤ 1.30 kV (Noted 1.35)
At Imax impuls current	≤ 1.72 kV
Measured limiting voltage 3kA/6 kV (1.2/50μs) Umax	≤ 0.90 kV
TOV behaviour	
L-N UT:	440 V (120 min)
Mounting connection	35mm DIN rail
fine*/-solid strand	For M5 biconnect terminal blocks
	0.5-25 mm² / 0.5-35 mm²
Terminal Screw Torque	2.0 N.m
Test force	≥ 100N



DHO 40-275(1+0)-FM

* fine strand wires must furnish with ferrules

Strip length

14.5mm

PE connection M5 2.0N.m

Remote warning contact (only -FM case)

single-pole change-over contact

plugable MC 1,5/3 ST

Fine-/solid strand

1,5/1,5 mm² / AWG 26-16

Spec/torque/dimension

M2 / 0,25 N.m / 7 mm

Max. operating voltage

250 VAC

Max. operating current

0.75 A AC

Response time tA (L-PE)

≤ 25 ns

Max. required fuse : series wiring/parallel wiring

80A gL/gG,

Temperature range

-40°C...+85°C (100°C pass)

Type of protection according to IEC 60529

IP20

Clearances and creepage distances according

To EN 60664-1:2003

≥ 6mm

Contamination level

2

Overvoltage category

III

Altitude

4000 m

And IEC / EN 61643-11

Test class EN/IEC

T1/I&T2/ II

Insulating material

Housing

PA 66

Inflammability class in acc. To UL 94

V0

In accordance to test standards

IEC 61643-11 GB18802.11

Verify Certification



Shanghai DHOCEAN Technology Co., Ltd.


202, Building 22, 1288 Luoning Road, Baoshan, Shanghai 200949, P.R. China

www.dhocean.cn


info@dhocean.cn

DHO 40-275(1+0)-FM

Diagram




Dimensions



Direction for Use

- The DC/AC SPD must be installed by an electrically skilled electrician. The installation position can not be directly touched by hands. Installation and connection to service must be done only when the system is de-energized. Check whether the SPD is in good condition, Red light indicates fault and the SPD needs replacement; Green light on in the notice window indicates normal.
- Install according to the wiring diagram and the installation requirements of SPD in GB 16895.22/IEC 60364-5-53, Grounding Conductor Cross-Sectional Area should not be less than 16mm². Consideration shall be given to limit the total wiring length of conductors between connection points of the SPD assembly to a value not greater than 0.5 m.
- Connection of remote warning contact: The SPD of the power module is equipped with a remote warning contact interface (11-12 is normally closed; 11-14 is normally open), can be used for remote centralized monitoring or alarming.
- After the wiring completed, check whether the module is assembled in place (if yes, 11-12 is closed, and 11-14 is disconnected). If No, re-press the module.

Connection Diagram



DHO 40-275(1+0)-FM

Operation and maintenance

- DHO 40-275(1+0)-FM After the power module SPD fails to work, it is automatically separated from the power supply line through the thermal fuse protection system inside the module, the display window changes from "green" to "red", and 11-12 of the remote contact interface is disconnected; 11- 14 is closed. When the deterioration indication window of the SPD power module is "red" or occurs a remote alarm signal, the SPD should be replaced by professionals immediately.
- **After a thunderstorm, check the SPD's display window on the power module.**

Packaging transportation and storage

- **Packaging:** Each SPD power module is packaged independently attached Series User Manual.
- **Transportation:** The product should have a covering during transportation, and should be no violent vibration and impact.
- **Storage:** Product storage temperature during -40 °C ~ 85 °C, relative humidity 5% ~ 95%. The warehouse is well ventilated, the floor is dry, and there is no corrosive gas. Products with a storage period of more than a year should be re-inspected before they are qualified for use.

